



HOS WARHORSE

400ES Multi-Purpose Service Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	362 ft 0 in (110.34 m)	Beam:	76 ft 0 in (23.16 m)	Draft Max:	20 ft 6in (6.25 m) (Est.)
LOA:	400 ft 0 in (121.92 m)			Draft Min:	11 ft 3 in (3.43 m) (Est.)
Gross:	6533 (Est.)	Net:	TBD		
IMO:	9696591	O.N.:	1258860	Flag:	U.S.
Certifications:	Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L				
Classifications:	ABS, *A1, OSV (HLC, HNLS, HDC), *AMS, *DPS-2, SPS, RRDA, HELIDK, *ACCU, UWILD, FFV-I, (E), ENVIRO, GP, CRC, Loadline				

PERFORMANCE

Cruise Speed:	10.0 kts	139 gal/hr (526 l/hr) (Est)
On DP:		117 gal/hr (443 l/hr) (Est)

PROPULSION, MACHINERY AND STEERING

Main Generators:	4 x Caterpillar 3516C	Total Power:	9,000 kW
Aux Generators:	2 x Caterpillar 3516C	Total Power:	3,450 kW
Main Propulsion:	2 x Schottel Azimuthing Z-Drives	Total Horsepower:	6,705 hp
Aft Bow Thruster:	1 x Schottel Drop-down Azimuth	Total Horsepower:	1,180 hp
Fwd Bow Thruster:	2 x Schottel FPP Tunnel	Total Horsepower:	2,360 hp
Stern Thruster:	1 x Schottel FPP Tunnel	Total Horsepower:	1,180 hp
		Power Generation:	690V/60/3 phase

CAPACITIES AND DELIVERY RATES

Deadweight:	6,265 LT (6,366 MT) (Est.)	Deck Area:	205 ft 4 in x 74 ft 9 in (13,600 ft ²) (Est.)
Deck Cargo:	2,750 LT (2,794 MT) (Est.)	Deck Load Rating:	63 m x 23 m (1,264 m ²) (Est.)
Liquid Mud:	11,324 bbl (1,800 m ³) (Est.)	Discharge Rate:	2,048 lbs/ft ² (10 MT/m ²)
Flamm/Methanol:	4,894 bbl (778 m ³) (Est.)	Discharge Rate:	2 X 1,000 GPM (227 m ³ /hr)
Potable Water:	178,312 gal (675 m ³) (Est.)	Discharge Rate:	2 x 250 GPM (57 m ³ /hr)
Rig Fuel:	561,311 gal (2,125 m ³) (Est.)	Discharge Rate:	4 X 300 GPM (68 m ³ /hr)
Rig Water:	766,226 gal (2,900 m ³) (Est.)	Discharge Rate:	1 x 200 GPM (45 m ³ /hr)
Cooler Area:	1050 ft ³ (30 m ³)	Discharge Rate:	2 X 750 GPM (170 m ³ /hr)
Off Ship Firefighting Monitors:	2	Discharge Rate:	2 X 750 GPM (170 m ³ /hr)
		Freezer Area:	2420 ft ³ (69 m ³)
		Total Flow Rate:	5,284 GPM (1,200 m ³ /hr) each

ELECTRONICS

Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, Speed Log, DGPS w/AIS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/loudhailer, SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, AIS, Cyscan, Radascan, DSDL, SSAS, VSAT

ACCOMMODATIONS

46 air conditioned/heated staterooms certified for 102 person berthing
Accommodations Include: 25 Office Stations, 3 Client Offices, Gym, Conference Room/Cinema for 18 Persons
Dedicated ROV Control Room and ROV Workshop

SPECIAL FEATURES

Helideck Diameter:	68 ft 11 in (21.0 m)	Size Rating:	Sikorsky S-61N
Helideck Equipment:	Restart Capability	Weight Rating:	Sikorsky S-92N, (12.8 MT)
Knuckle Boom Crane:	Main Line: w/ Active Heave Compensation ABS / API 2C Certified	Max Lift @ Max Radius:	65 Mt @ 114 ft 10 in
	Whip Line: w/ Active Heave Compensation Personnel Lift Certified	Max Lift @ Min Radius:	250 Mt @ 27 ft 3 in
Knuckle Boom Crane:	NOV w/ Active Heave Compensation	Max Lift @ Max WD:	92.3 Mt @ 12,140 ft WD
		Max Lift @ Max Height:	163 Mt @ 136 ft 3 in abv MD
Deck Crane:	1 x Appleton EB70-53-33 Personnel Lift Certified	Max Lift @ Max Radius:	25 Mt @ 118 ft 1 in
Fast Rescue Craft:	1 x 15 Person(s)	Max Lift @ Max WD:	4.56 Mt @ 12,140 ft WD
Moon Pool:	15ft x 18ft with Hatch	Max Lift @ Max Radius:	29.2 Mt @ 95 ft 0 in
ROV:	2 x 250 HP Work Class (TBD)	Max Lift @ Min Radius:	70 Mt @ 25 ft 0 in (1 fall) 100 Mt @ 25 ft 0 in (2 falls)
		Max Lift @ Max Depth:	49 Mt @ 6,580 ft WD
		Max Lift @ Max Radius:	3 Mt @ 53 ft
		Max Lift @ Max Radius:	13 Mt @ 16 ft
		Tuggers:	2 x 12 Mt
		Watermaker Capacity:	8,000 USG/day
		DP Reference:	1 x Kongsberg HiPAP 500

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck Offshore does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck Offshore accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.